



# Laser distance meters

## HDM-50G/-70G/-90G



### Work comfort

very good visible green laser



### Reliable measurements

fast and precise processor



### Easy to use

large, backlit display



### Resistant to damage

safe use for years



### Data transmission

bluetooth, USB



## Laser distance meters

HDM-50G HDM-70G HDM-90G

|   |                        |      |      |
|---|------------------------|------|------|
| <b>Working range</b>                    | 50 m                   | 70 m | 90 m |
| <b>Measuring accuracy</b>               | ±2 mm                  |      |      |
| <b>Laser type</b>                       | green, class II, <1 mW |      |      |
| <b>The wavelength of the laser</b>      | 535 nm                 |      |      |
| <b>MAX &amp; MIN Value</b>              | ✓                      |      |      |
| <b>Area, volume</b>                     | ✓                      |      |      |
| <b>„Painter“ function</b>               | ✓                      |      |      |
| <b>Pythagoras measuring</b>             | ✓                      |      |      |
| <b>Sum, subtracking</b>                 | ✓                      |      |      |
| <b>Value min. and max</b>               | ✓                      |      |      |
| <b>Skating-out</b>                      | ✓                      |      |      |
| <b>Delay measurement</b>                | ✓                      |      |      |
| <b>Self-calibration</b>                 | ✓                      |      |      |
| <b>Bubble</b>                           | ✓                      |      |      |
| <b>Backlight</b>                        | ✓                      |      |      |
| <b>Record</b>                           | 100                    |      |      |
| <b>Auto switch off</b>                  | ✓                      |      |      |
| <b>Working temperature</b>              | 0-+40°C                |      |      |
| <b>Storage temperature</b>              | -20-+60°C              |      |      |
| <b>Resistance class</b>                 | IP54                   |      |      |
| <b>Foot (measurement in the corner)</b> | ✓                      |      |      |
| <b>Power supply</b>                     | Ni-MH 3x1,2V 800 mAh   |      |      |
| <b>Dimensions</b>                       | 118x54x28 mm           |      |      |
| <b>Weight</b>                           | 132 g                  |      |      |

### Large measurement capabilities

With the ability to record up to 100 values - range-finders software can measure distances and perform calculations on their basis (such as addition, subtraction, area and volume)

### Additional features

„Painter“ function, skating-out, continuous measurement / min. - max. function, delay measurement, self-calibration - measurement's support in construction

### Work from the edge

Measurements can be performed from the rangefinder front, base or foot (measurements in the corner)

### Intuitive, small and handy

The measurement is done at the touch of a button, shortcut keys speed up access to frequently used functions. Fit in any pocket, handy housing provides a sure grip.

### Measure the unavailable spaces

Pythagoras function allows you to pursue an indirect measure of the height or width.

### Equipment

|                      |            |
|----------------------|------------|
| Laser distance meter | Belt       |
| Disc                 | USB cable  |
| Batteries set        | Manual     |
| Case                 | Carton box |



Your local distributor